			ICO7 Rec'd PCTIPTO 2 1 MAR 2002
FORM PTÖ (REV 11-20	100)	T OF COMMERCE PATENT AND TRADEMARK OFFIC	ATTORNEY'S DOCKET NUMBER
	TRANSMITTAL LETTER	TO THE UNITED STATES	66309-145-2
		ED OFFICE (DO/EO/US)	U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR
		NG UNDER 35 U.S.C. 371	10/088669
INTERN.	ATIONAL APPLICATION NO.	INTERNATIONAL FILING DATE	
	PCT/IB00/01452	September 29, 2000	PRIORITY DATE CLAIMED October 1, 1999
	F INVENTION		2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2
BRAK	ING UNIT FOR BICYCLES		
	NT(S) FOR DO/EO/US		
Massin	no PERUZZO and Gilberto PA	ROLIN	
Applicar	at herewith submits to the United Sta	ates Designated/Elected Office (DO/EO/US	S) the following items and other information:
1.		items concerning a filing under 35 U.S.C. 3	
2.		QUENT submission of items concerning a f	
,3. Z	This is an express request to beg	gin national examination procedures (35 II)	S.C. 371(f)). The submission must include itens (5), (6),
	(2) and (24) indicated below.		
4. □ 5. □		expiration of 19 months from the priority d	late (Article 31).
5. Z	A copy of the International App	lication as filed (35 U.S.C. 371 (c) (2))	
1	 a. is attached hereto (requ 	aired only if not communicated by the Inter	rnational Bureau).
4	b. as been communicated	d by the International Bureau.	
". "6. Z		application was filed in the United States Re	
"6. Z	An English language translation	of the International Application as filed (33	5 U.S.C. 371(c)(2)).
	a. 🛮 is attached hereto.		
	b. has been previously sul	bmitted under 35 U.S.C. 154(d)(4).	
.J7. □		e International Application under PCT Artic	
h ``		quired only if not communicated by the Inte	ernational Bureau).
de de la constitución de la cons		ed by the International Bureau.	
ul.	c. have not been made; ho	owever, the time limit for making such amen	ndments has NOT expired.
	d. have not been made and		
8.	An English language translation	of the amendments to the claims under PCT	T Article 19 (35 U.S.C. 371(c)(3)).
9.			
0.	An English language translation Article 36 (35 U.S.C. 371 (c)(5))	of the annexes to the International Prelimin	nary Examination Report under PCT
1.	A copy of the International Prelin	minary Examination Report (PCT/IPEA/40)	9).
2.	A copy of the International Search	h Report (PCT/ISA/210).	
Items	13 to 20 below concern document	(s) or information included:	
3.	An Information Disclosure State	ment under 37 CFR 1.97 and 1.98.	
4. Z	An assignment document for reco	ording. A separate cover sheet in compliance	ce with 37 CFR 3.28 and 3.31 is included
5. Z	A FIRST preliminary amendmen	ıt.	
6. □	A SECOND or SUBSEQUENT	preliminary amendment.	i
7.	A substitute specification.		i
8.	A change of power of attorney an	d/or address letter.	
9.	A computer-readable form of the	sequence listing in accordance with PCT R	Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
0.	A second copy of the published in	nternational application under 35 U.S.C. 15	54(d)(4).
1. 🗆	A second copy of the English lang	guage translation of the international applic	
2. 🗆	Certificate of Mailing by Express	Mail	
3.	Other items or information:		
	Small Entity Declaration; 6 shee	ets of drawings; PCT Written Opinion; V	VO 01/24885.

JC13 Rec'd PCT/PTO 2 1 MAR 2002 U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 9INTERNATIONAL APPLICATION NO. ATTORNEY'S DOCKET NUMBER PCT/IP00/01452 66309-145-2 24. The following fees are submitted:. CALCULATIONS PTO USE ONLY BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) : Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1040.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the ÉPO or JPO \$890.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO \$740.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4)..... \$710.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4)..... \$100.00 ENTER APPROPRIATE BASIC FEE AMOUNT = \$890.00 Surcharge of \$130.00 for furnishing the oath or declaration later than □ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)). \$0.00 **CLAIMS** NUMBER FILED NUMBER EXTRA RATE Total claims -20 =\$18.00 \$0.00 dependent claims -3 =0 \$84.00 \$0.00 Multiple Dependent Claims (check if applicable). \$0.00 TOTAL OF ABOVE CALCULATIONS \$890.00 Applicant claims small entity status. See 37 CFR 1.27). The fees indicated above are reduced by 1/2. \$445.00 SUBTOTAL \$445.00 rocessing fee of \$130.00 for furnishing the English translation later than □ 20 □ 30 nonths from the earliest claimed priority date (37 CFR 1.492 (f)). \$0.00 TOTAL NATIONAL FEE \$445.00 tee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). \$40.00 TOTAL FEES ENCLOSED \$485.00 Amount to be: refunded \$ charged \$ a. A check in the amount of to cover the above fees is enclosed. b. \mathbf{X} Please charge my Deposit Account No. 04-2223____ in the amount of \$485.00 to cover the above fees. A duplicate copy of this sheet is enclosed. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment c. to Deposit Account No. 04-2223 A duplicate copy of this sheet is enclosed. Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card d. information should not be included on this form. Provide credit card information and authorization on PTO-2038. NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status. SEND ALL CORRESPONDENCE TO: John P. DeLuca

DYKEMA GOSSETT PLLC Third Floor West, Franklin Square 1300 I Street, N.W. Washington, DC 20005-3306 (202) 906-8600

SIGNATURE	
John P. Del uca	
NAME	
25,505	

REGISTRATION NUMBER

66309-145-2

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)	PATENT	•
Massimo PERUZZO et al.)	Group:	Unassigned
Serial No. Unassigned)	Examiner:	: Unassigned
Filed: Herewith)		
BRAKING UNIT FOR RICYCLES)		

PRELIMINARY AMENDMENT

Washington, D.C. March 21, 2002

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

Prior to examination on the merits, please amend the Application as follows:

IN THE CLAIMS:

Please amend the claims as follows:

1. (Amended) A braking assembly for bicycles (B) particularly adapted for training of cyclists, constrained to a support structure and provided with braking means cooperating with the driving wheel (R) of said bicycle (B) to generate a resisting torque opposing the rotation applied by the cyclist to said driving wheel (R) through the pedals (P), said braking means comprising at least a flexible belt with mainly longitudinal development arranged with perimetral adherence to tyre (C) of said driving wheel (R) for at least a portion of its circumference and wound as a closed loop between at least a couple of to revolving rollers, at least one of said rollers being operatively connected to energy dissipation means, said couple of revolving rollers being part of a rigid frame supported by a support bracket constrained to said support structure, said couple of revolving

-1 . 1

rollers comprising a first roller operatively connected to said energy dissipation means and a second roller, said flexible belt being wound between said rollers, said rollers having substantially horizontal and parallel rotation axes, said rigid frame being connected to said support bracket through adjustment means adapted to change its position in respect of said type (C) of said driving wheel (R), wherein said energy dissipation means comprise a disc of a magnetic material fixedly keyed to said first roller with the surface arranged, between a couple of magnetic pieces supported by a moveable fork integral with said rigid frame and connected to actuating means adapted to move said magnetic pieces in respect of said disc.

- 2. (Amended) The braking assembly according to claim 1, wherein said amagnetic disc is connected to said first roller through a fly wheel with cooling fan, both coaxial with said first roller.
- 3. (Amended) The braking assembly according to claim 1, wherein said disc of amagnetic material is arranged inside a case fixed to said rigid frame and provided with guide means for sliding said moveable fork.
- 4. (Amended) The braking assembly according to claim 1, wherein said actuating means comprise a flexible wire fixed at one end to said moveable fork and at the opposite end to a control lever supported by the handlebar of said bicycle (B).
- 5. (Amended) The braking assembly according to claim 1, wherein said rigid frame is connected to said support bracket also through blocking means adapted to fix said frame in the position defined by said adjustment means.

- 6. (Amended) The braking assembly according to claim 1, wherein said adjustment means comprise at least a screw with control means integral with said support bracket, said screw being coupled with a nut-screw fixed to said rigid frame.
- 7. (Amended) The braking assembly according to claim 5, wherein said blocking means comprise at least a screw protruding from said rigid frame and threaded in a slit made in said support bracket to which is fixed through a nut-screw with control handle.
- 8. (Amended) The braking assembly according to claim 1, wherein said first roller on its outer surface has grooves cooperating with corresponding grooves made on the inner surface of said flexible belt.
- 9. (Amended) The braking assembly according to claim 1, wherein said revolving rollers have the corresponding rotation axes arranged at the same distance (d) from the hub of said driving wheel (R) for any position in which said frame places the flexible belt adhering to said tyre (C).
- 10. (Amended) The braking assembly according to claim 1, wherein said rigid frame comprises a couple of parallel side members rigidly connected to one another through a couple of fixed pins each of them being the pivot pin of a corresponding roller.
- 11. (Amended) The braking assembly according to claim 1, wherein said support bracket consists of a couple of facing half brackets between which said rigid frame is arranged.

12. (Amended) The braking assembly according to claim 11, wherein said support bracket is fixed to a support stand supporting said bicycle (B) arranging it in a vertical fixed position with the driving wheel (R) raised from the ground (T).

13. (Amended) The braking assembly according to claim 12, wherein said support stand supports said bicycle (B) at the hub (M) of the driving wheel (R).

14. (Amended) The braking assembly according to claim 11, wherein said support bracket is fixed to the back fork (F) of the frame of said bicycle (B).

Please remove multiple dependencies from the claims. If any multiple dependent claims remain after amendment, such multiple dependent claims should refer only to the next previous claim.

REMARKS

This Amendment is for the purpose of removing multiple dependencies and reference numerals from the claims and for placing the claims in appropriate U.S. format.

Allowance of the claims is earnestly solicited.

If filing this paper or any accompanying papers necessitates additional fees not otherwise provided for, the undersigned authorizes the Commissioner to deduct such additional fees from Deposit Account No. 04-2223.

Respectfully submitted,

John P. De Luca

Registration No. 25,505

DYKEMA GOSSETT PLLC 1300 I STREET N.W. SUITE 300 W WASHINGTON, D.C. 20005 (202) 906-8600

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS:

1[)]. (Amended) A braking assembly [(1)] for bicycles (B) particularly adapted for training of cyclists, constrained to a support structure [(2;F)] and provided with braking means [(3)] cooperating with the driving wheel (R) of said bicycle (B) to generate a resisting torque opposing the rotation applied by the cyclist to said driving wheel (R) through the pedals (P), said braking means [(3)] comprising at least a flexible belt [(4)] with mainly longitudinal development arranged with perimetral adherence to tyre (C) of said driving wheel (R) for at least a portion of its circumference and wound as a closed loop between at least a couple of to revolving rollers [(5, 6)], at least one of said rollers being operatively connected to energy dissipation means [(7)], said couple of revolving rollers [(5, 6)] being part of a rigid frame [(8)] supported by a support bracket [(9)] constrained to said support structure [(2; F)], said couple of revolving rollers comprising a first roller [(5)] operatively connected to said energy dissipation means [(7)] and a second roller [(6)], said flexible belt [(4)] being wound between said rollers, said rollers [(5, 6)] having[,] substantially horizontal and parallel rotation axes [(5b, 6b)], said rigid frame [(8)] being connected to said support bracket [(9)] through adjustment means [(110)] adapted to change its position in respect of said type (C) of said driving wheel (R), wherein said energy dissipation means [(7)] comprise a disc [(14)] of a magnetic material fixedly keyed to said first roller [(5)] with the surface arranged, between a couple of magnetic pieces [(17a, 17b)] supported by a moveable fork [(18)] integral with said rigid frame [(8)] and connected to actuating means [(22)] adapted to move said magnetic pieces [(17a, 17b)] in respect of said disc [(14)].

2[)]. (Amended) The braking assembly [(1)] according to claim 1[)], wherein said amagnetic disc [(14)] is connected to said first roller [(5)] through a fly wheel [(15)] with cooling fan [(16)], both coaxial with said first roller [(5)].

- 3[)]. (Amended) The braking assembly [(1)] according to claim 1[)], wherein said disc of amagnetic material [(14)] is arranged inside a case [(20)] fixed to said rigid frame [(8)] and provided with guide means [(19)] for sliding said moveable fork [(18)].
- 4[)]. (Amended) The braking assembly [(1)] according to claim 1[)], wherein said actuating means [(22)] comprise a flexible wire [(22a)] fixed at one end to said moveable fork [(18)] and at the opposite end to a control lever [(22b)] supported by the handlebar of said bicycle (B).
- 5[)]. (Amended) The braking assembly [(1)] according to claim 1[)], wherein said rigid frame [(8)] is connected to said support bracket [(9)] also through blocking means [(11)] adapted to fix said frame in the position defined by said adjustment means [(10)].
- 6[)]. (Amended) The braking assembly [(9)] according to claim 1[)], wherein said adjustment means [(10)] comprise at least a screw [(24, 25)] with control means [(24a, 25a)] integral with said support bracket [(9)], said screw being coupled with a nut-screw [(29, 30)] fixed to said rigid frame [(8)].
- 7[]. (Amended) The braking assembly [(1)] according to claim 5[)], wherein said blocking means [(11)] comprise at least a screw [(31, 32)] protruding from said rigid frame [(8)] and threaded in a slit [(33, 34)] made in said support bracket [(9)] to which is fixed through a nutscrew [(35, 36)] with control handle [(35a, 36a)].

8[)]. (Amended) The braking assembly [(1)] according to claim 1[)], wherein said first roller [(5)] on its outer surface has grooves [(5a)] cooperating with corresponding grooves [(4a)] made on the inner surface of said flexible belt [(4)].

9[)]. (Amended) The braking assembly [(1)] according to claim 1[)], wherein said revolving rollers [(5, 6)] have the corresponding rotation axes [(5b, 6b)] arranged at the same distance (d) from the hub of said driving wheel (R) for any position in which said frame [(8)] places the flexible belt [(4)] adhering to said tyre (C).

10[)]. (Amended) The braking assembly [(1)] according to claim 1[)], wherein said rigid frame [(8)] comprises a couple of parallel side members [(8a, 8b)] rigidly connected to one another through a couple of fixed pins [(12, 13)] each of them being the pivot pin of a corresponding roller [(5, 6)].

11[)]. (Amended) The braking assembly [(1)] according to claim 1[)], wherein said support bracket [(9)] consists of a couple of facing half brackets [(26, 27)] between which said rigid frame [(8)] is arranged.

12[)]. (Amended) The braking assembly [(1)] according to claim 11[)], wherein said support bracket [(9)] is fixed to a support stand [(2)] supporting said bicycle (B) arranging it in a vertical fixed position with the driving wheel (R) raised from the ground (T).

13[)]. (Amended) The braking assembly [(1)] according to claim 12[)], wherein said support stand [(2)] supports said bicycle (B) at the hub (M) of the driving wheel (R).

14[)]. (Amended) The braking assembly [(1)] according to claim 11[)], wherein said support bracket [(9)] is fixed to the back fork (F) of the frame of said bicycle (B).

50313.1

9

20

25

35

ÎB0001452 10088669

-1-

BRAKING UNIT FOR BICYCLES

The invention relates to a bicycle braking assembly to carry out training of cyclists.

It is known that cyclists wanting to train using their own bicycle, are using proper braking assemblies that are engaged with the driving wheel to obtain an adjustable resisting torque opposing its rotation carried out with the pedals. GB-475207 discloses an excercises machine, particularly a bicycle, where the driving wheel engages and drives a movable support comprising an endless band carried by rollers.

More particularly the braking assemblies of known type are applied to braking 10 stands used in gymnasia and generally in closed rooms, comprising a tripod supporting the bicycle which is arranged in a vertical position with the driving wheel raised from the ground and engaged with the braking means.

According to the state of the art devices, the braking assemblies comprise one or more; rollers with a substantially horizontal axis contacting the tyre of the driving wheel and connected to an electromagnetic, hydraulic or mechanical brake provided with regulation means adapted to change the resisting torque. The above mentioned braking assemblies however have some drawbacks.

A first drawback consists in that in use a friction is generated between the wheel and the braking rollers so that the tyre is quickly deteriorated.

Since primarily in racing bicycles the tyres are made of special materials and therefore are particularly expensive, this is clearly an unnecessary rise of costs for the user.

A further drawback consists in that in use a considerable noise is generated that sometimes cannot be tolerated for instance when the braking assembly is applied on braking stands used in gymnasia and generally in closed rooms.

Use of the above mentioned braking assemblies is particularly problematic when they are used with bicycles like mountain bikes provided with tyres having a tread with deep grooves.

In such a case in addition to the considerable wear of the tyre of the driving 30 wheel and greater operation noise, annoying vibrations are also generated, that are transmitted to bicycle and cyclist who is obliged to pedal in uncomfortable conditions.

In an effort to remove such drawbacks, braking assemblies were made in which the braking rollers are contacted with the rim of the driving wheel instead The state of the s

- 1a -

of the tyre.

More particularly the braking assembly comprises a couple of opposed contrasting rollers that are holding a grip with the edge of the rim of the driving

Emotans AMENDED SHEET

15

25

30

35

of the tyre.

More particularly the braking assembly comprises a couple of opposed contrasting rollers that are holding a grip with the edge of the rim of the driving wheel that is kept raised from the ground by a stand fixed to the hub.

The above mentioned braking assemblies with opposed rollers and related braking stands are actually solving the problem of noise and tyre wear and can be used both for racing bicycles and bicycles of mountain bike type.

However these assemblies have further drawbacks, one being the fact that braking assemblies with lateral rollers have costs that are considerably higher than the braking assemblies with rollers tangent to the wheel and this is due to their greater mechanical complexity.

A further drawback consists in that fitting the bicycle on the braking stand using said braking assemblies, is less easy and quick because it is necessary to use a particular device being part of the braking assembly, adapted to spread the contrasting rollers in order to place the wheel between the rollers.

Last but not least drawback consists in that a friction is generated between rim and rollers, obliging user to replace said rollers from time to time in order to keep the braking assembly always perfectly efficient.

The present invention aims to remove said drawbacks.

More particularly, a first object of the invention is a bicycle braking assembly that reduces considerably wear of the tyre of the driving wheel contacting the braking means in comparison with the braking assemblies of equivalent known type.

Another object of the invention is a braking assembly having an operation noise lower than the braking assemblies of equivalent known type.

A further object of the invention is a braking assembly inducing less vibrations in the bicycle in use.

Still a further object of the invention is a braking assembly of simpler construction and with more reliable operation in comparison with braking assemblies of known type available on the market and with corresponding performances.

These objects are attained by a bicycle braking assembly particularly suitable for training of cyclists, that according to the main claim is constrained to a support structure and is provided with braking means cooperating with the bicycle driving wheel so as to generate a resisting torque opposing the rotation

25

35

applied by the cyclist to said driving wheel through the pedals wherein said braking means comprise at least a flexible belt with mainly longitudinal development arranged with a perimetral adherence to tyre

of said driving wheel for at least a portion of its circumference and wound as a closed loop between at least a couple of rotating rollers, at least one of said rollers being operatively connected to energy dissipation means.

According to a preferred embodiment the rotating rollers are belonging to a rigid frame supported by a support bracket which is constrained to the support structure.

The braking assembly is preferably used with a braking stand comprising a tripod supporting the bicycle at the hub of the driving wheel and keeping the bicycle in a vertical position with the driving wheel raised from the ground.

The tripod is the support structure to which the support bracket of the braking assembly is fixed.

Proper adjustment means of the screw and nut screw type allow to change the position of the rigid frame and consequently of the flexible belt in respect of the driving wheel so as to adjust the braking stand to the different size of the bicycles.

The couple of revolving rollers comprises a first roller with an internal grooved surface connected to energy dissipation means and a second roller with outer smooth surface, parallel to one another and revolving around fixed rotation axes of the rigid frame.

The energy dissipation means comprise a disc of amagnetic material, preferably aluminum, fixedly keyed to the first roller and arranged between a couple of magnetic pieces supported by a moveable fork that can be moved by actuating means in respect of the disc. Such actuating means comprise an operating lever fixed to the bicycle frame and driving a flexible wire that moves the fork so as to change the surface area of the magnetic pieces and of the facing disc.

According to a mentioned embodiment the braking assembly of the invention may be applied to a support stand of a bicycle arranged with the driving wheel raised from the ground, so as to obtain a braking stand allowing training of cyclists in gymnasium or in domestic rooms.

According to another embodiment, the braking assembly of the invention may be fixed to the bicycle frame so as to obtain braking of the driving wheel when

30

35

the bicycle is running on the road.

The braking assembly of the invention advantageously shows a quieter operation and reduces tyre wear in view of the elastic contact between tyre and belt.

The braking assembly of the invention is also more reliable than the braking assemblies of known type as it comprises a lower number of components.

The braking assembly of the invention has also a less expensive construction and requires less maintenance in respect of the braking assemblies of equivalent known type.

- The foregoing objects and advantages will be better understood from the description of a preferred embodiment of the invention that is given as an illustrative non-limiting example with reference to the accompanying sheets of drawings in which:
 - FIG. **1** is a side view of the braking assembly of the invention applied to a bicycle arranged in a fixed vertical position;
 - FIG. **2** is a vertical sectional view of a detail of the braking assembly and bicycle of FIG. **1**;
 - FIG. 3 is a sectional view taken along line III-III of another detail of the braking assembly of FIG. 1;
- FIG. 4 is an outer view of the detail of FIG. 3;
 - FIG. **5** is a sectional view along line V-V of a detail of the braking assembly of FIG. **1**; and
 - FIG. **6** is a view of a different application of the braking assembly of the invention.
- The braking assembly of the invention shown in FIG. 1 is generally indicated with reference number 1. The braking assembly is constrained to a support structure comprising a support stand generally indicated with reference number 2 for a bicycle B.

The braking assembly 1 together with the support stand 2 constitutes therefore a static braking stand for the bicycle B, where the braking assembly generates a resisting torque opposing the rotation that the cyclist gives to the driving wheel R actuating the pedals P.

According to the invention and with particular reference to FIGS. 2 and 3, the braking means 3 comprise a flexible belt 4 with a mainly longitudinal development arranged with a perimetral adherence to tyre C of the driving

15

20

25

30

35

wheel **R** for at least a portion of its circumference and wound as a closed loop between a couple of revolving rollers **5**, **6** one of which, more particularly the first revolving roller **5**, is operatively connected to energy dissipation means generally indicated with reference number **7**.

The revolving rollers **5**, **6** are part of a rigid frame generally indicated with **8** that can be seen also in FIG. **4**, and define a couple of longitudinal rotation axes **5b**, **6b** parallel to one another.

The rigid frame 8 is supported by a support bracket generally indicated with 9 and steadily fixed to stand 2, to which the rigid frame 8 is connected through adjustment means generally indicated with 10 adapted to change the position in respect of the driving wheel R.

Proper blocking means 11 are fixing the rigid frame 8 in the desired position.

More particularly it can be seen in FIG. 3 that the rigid frame 8 comprises a couple of side members 8a, 8b parallel to one another that are rigidly connected through a couple of fixed pins 12, 13, each of them being the pivot pin of a corresponding roller 5, 6 with the intermediate arrangement of rolling bearings 12a, 12b and 13a, 13b respectively.

More particularly the first roller 5 has an outer surface provided with grooves 5a cooperating with corresponding grooves 4a made on the inner surface of the flexible belt 4 while the second roller 6 has an outer smooth surface.

As already mentioned, the first roller 5 is connected to energy dissipation means generally indicated with reference number 7 comprising a disc 14 preferably made of amagnetic material for instance aluminum, fixedly keyed to the first roller through a fly wheel 15 and a cooling fan 16 which is arranged between a couple of magnetic pieces 17a, 17b supported by a moveable fork 18 sliding along guide means 19 of a case 20 fixed to the rigid frame 8.

More particularly case 20 has a protective function as it is so shaped as to contain disc 14, fly wheel 15, fan 16 and fork 18 as shown in FIG. 3.

Fork 18 may slide longitudinally along the guide means 19 in both directions of arrow 21 being connected to actuating means 22 comprising a flexible metal wire 22a tensioned by an operating lever 22b fixed to the bicycle handlebar.

With regard to the adjustment means generally indicated with 10, it can be seen in FIG. 5 that said means comprise a couple of screws 24, 25, each of them being integral with a corresponding half bracket 26, 27 and being coupled to a nut-screw 29, 30 fixed to the rigid frame 8 at a corresponding side

20

25

30

member 8a, 8b.

Each screw 24, 25 is arranged in through holes 8c, 8d made in each corresponding side member 8a, 8b and is provided at one end with a control hand-wheel 24a, 25a.

As to the blocking means generally indicated with 11 shown in FIGS. 3 and 4, it can be seen that said means comprise a couple of screws 31, 32 each protruding from the corresponding side member 8a, 8b of the rigid frame 8 and threaded in a corresponding slit 33, 34 shown in FIGS. 2 and 3 and made in each half-bracket 26, 27 which is fixed through a nut-screw 35, 36 preferably made in a control handle 35a, 36a.

Locking is obtained by lock-nuts 37, 38.

The position of the rigid frame 8 is adjusted by acting on the adjustment means 10 so as to cause the flexible belt 4 to adhere to tyre C of the driving wheel R.

Then the rigid frame 8 is fixed in the adjustment position so obtained through the locking means 11, so that rollers 5, 6 as shown in FIG. 2 do not contact said wheel and their longitudinal axes 5b, 6b are arranged at the same distance d from hub M of the driving wheel R.

The cyclist starts pedalling and actuating the lever 23 causes the fork 18 to slide arranging it in any position comprised between the two end positions shown with continuous line and dashed line in FIG. 3 according to the desired resisting force.

Indeed the magnetic pieces 17a, 17b carry out a magnetic effect induced on the aluminum disc 14 braking the first roller 5 and therefore the belt 4 in proportion to the opposite surface areas of the magnetic pieces and the aluminum disc.

A different application of the braking assembly 1 of the invention is shown in FIG. 6 where the assembly is constrained to the back fork F of the frame of the bicycle B that in this case constitutes the support structure.

With this application solution the cyclist may perform a dynamic training running with the bicycle on the road.

From the foregoing description it is to be understood that elasticity of contact between tyre **C** and flexible belt **4** reduces wear of tyre **C** and makes operation of the bicycle less noisy.

More particularly noise and wear do not change when on the braking stand racing bicycles or bicycles like mountain bikes with grooved tyre are installed.

It is also to be pointed out that the limited number of components simplifies the mechanical construction and reduces the corresponding costs as well.

Moreover, as the pivot pins of the rollers driving the flexible belt are fixed, a greater operation precision is allowed in comparison with the braking assemblies of known type in which on the contrary the pivot pins supporting the rollers are revolving pins.

Finally the braking assembly of the invention in both embodiments in which it is connected either to the stand supporting the bicycle **B** or to the back fork **F** of the bicycle frame, can be easily adjusted so as to regulate in an optimal way the adherence of the belt to the surface of the tyre of the driving wheel.

It is clear that modifications of structure and shape may be made in carrying out the braking assembly of the invention that should be covered by the present patent when falling in the scope of the appended claims.

15

20

30

35

CLAIMS

06-12-2201 001 18:58

- 1) A braking assembly (1) for bicycles (B) particularly adapted for training of cyclists, constrained to a support structure (2; F) and provided with braking means (3) cooperating with the driving wheel (R) of said bicycle (B) to generate a resisting torque opposing the rotation applied by the cyclist to said driving wheel (R) through the pedals (P), said braking means (3) comprising at least a flexible belt (4) with mainly longitudinal development arranged with perimetral adherence to tyre (C) of said driving wheel (R) for at least a portion of its circumference and wound as a closed loop between at least a couple of revolving rollers (5, 6), at least one of said rollers being operatively connected to energy dissipation means (7), said couple of revolving rollers (5, 6) being part of a rigid frame (8) supported by a support bracket (9) constrained to said support structure (2; F), said rigid frame (8) being connected to said support bracket (9) through adjustment means (10) adapted to change its position in respect of said tyre (C) of said driving wheel (R), characterized in that said energy dissipation means (7) comprise a disc (14) of amagnetic material fixedly keyed to said first roller (5) with the surface arranged between a couple of magnetic pieces (17a, 17b) supported by a moveable fork (18) integral with said rigid frame (8) and connected to actuating means (22) adapted to move said magnetic pieces (17a, 17b) in respect of said disc (14).
- 2) The braking assembly (1) according to claim 1) characterized in that said amagnetic disc (14) is connected to said first roller (5) through a fly wheel (15) with cooling fan (16), both coaxial with said first roller (5).
- 3) The braking assembly (1) according to claim 1) characterized in that said disc of amagnetic material (14) is arranged inside a case (20) fixed to said rigid frame (8) and provided with guide means (19) for sliding said moveable fork (18).
- 4) The braking assembly (1) according to claim 1) characterized in that said actuating means (22) comprise a flexible wire (22a) fixed at one end to said moveable fork (18) and at the opposite end to a control lever (22b) supported by the handlebar of said bicycle (B).
- 5) The braking assembly (1) according to claim 1) characterized in that said rigid frame (8) is connected to said support bracket (9) also through blocking means (11) adapted to fix said frame in the position defined by said adjustment means (10).

10

15

20

25

30

35

ķ

-9-

- 6) The braking assembly (1) according to claim 1) characterized in that said adjustment means (10) comprise at least a screw (24, 25) with control means (24a, 25a) integral with said support bracket (9), said screw being coupled with a nut-screw (29, 30) fixed to said rigid frame (8).
- 7) The braking assembly (1) according to claim 5) characterized in that said blocking means (11) comprise at least a screw (31, 32) protruding from said rigid frame (8) and threaded in a slit (33, 34) made in said support bracket (9) to which is fixed through a nut-screw (35, 36) with control handle (35a, 36a).
- 8) The braking assembly (1) according to claim 1) characterized in that said couple of revolving rollers comprises a first roller (5) operatively connected to said energy dissipation means (7) and a second roller (6), said flexible belt (4) being wound between said rollers, said rollers (5, 6) having substantially horizontal and parallel rotation axes (5b, 6b).
- 9) The braking assembly (1) according to claim 8) characterized in that said first roller (5) on its outer surface has grooves (5a) cooperating with corresponding grooves (4a) made on the inner surface of said flexible belt (4).
- 10) The braking assembly (1) according to claim 1) characterized in that said revolving rollers (5, 6) have the corresponding rotation axes (5b, 6b) arranged at the same distance (d) from the hub of said driving wheel (R) for any position in which said frame (8) places the flexible belt (4) adhering to said tyre (C).
- 11) The braking assembly (1) according to claim 1) characterized in that said rigid frame (8) comprises a couple of parallel side members (8a, 8b) rigidly connected to one another through a couple of fixed pins (12, 13) each of them being the pivot pin of a corresponding roller (5, 6).
- 12) The braking assembly (1) according to claim 1) characterized in that said support bracket (9) consists of a couple of facing half brackets (26, 27) between which said rigid frame (8) is arranged.
- 13) The braking assembly (1) according to claim 12) characterized in that said support bracket (9) is fixed to a support stand (2) supporting said bicycle (B) arranging it in a vertical fixed position with the driving wheel (R) raised from the ground (T).
- 14) The braking assembly (1) according to claim 13) characterized in that said support stand (2) supports said bicycle (B) at the hub (M) of the


driving wheel (R).


15) The braking assembly (1) according to claim 12) characterized in that said support bracket (9) is fixed to the back fork (F) of the frame of said bicycle (B).


The court of the c


ABSTRACT


A braking assembly (1) for bicycles (B) is disclosed, particularly suitable for training of cyclists, constrained to a support structure (2; F) and provided with braking means (3) cooperating with the driving wheel (R) of said bicycle (B) to generate a resisting torque opposing the rotation given by the cyclist to the driving wheel (R) through the pedals (P). The braking means (3) comprise a flexible belt (4) with mainly longitudinal development arranged with perimetral adherence to tyre (C) of the driving wheel (R) for at least a portion of its circumference and wound as a closed loop between at least a couple of revolving rollers (5, 6), one of said rollers being operatively connected to energy dissipation means (7).














COMBINED DECLARATION AND POWER OF ATTORNEY FOR **UTILITY** PATENT APPLICATION (Includes PCT)

Attorney Docket No.

As a below named inventor, I hereby declare that: My residence, post office address and citizenship are as stated below next to my name; that

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural inventors are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: BRAKING UNIT FOR BICYCLES

the specification of which (check one): [X] is attach	ed hereto.		
[] was filed on	as Application	n Serial No ar	nd was a	nmended
on	·			
[] was filed as PCT interpretation	mational application no(if	and was applicable).		
Thereby state that I have r	eviewed and understand the	contents of the above-identified sp	accificati	on including the all-i
as amended by any amend	dment referred to above.	oontones of the above-identified sp	Decincati	on, including the claims,
Facknowledge the duty to title 37, Code of Federal R	disclose information which i Regulations, §1.56(a).	s material to the examination of thi	s applica	ation in accordance with
do not know and do not b	elieve the claimed invention	was ever known or used in the Unit	ted State	es of America before my
of America more than one your America more than one inventor's certificate issued	or patented or described in ear prior to this application, year prior to this application, before the date of this appl	any printed publication in any couthat the same was not in public use that the invention has not been patication in any country foreign to the ssigns more than twelve months pri	ntry before or on second or on the secon	ore my or our invention sale in the United States made the subject of an States of America on an
inventor's certificate listed	ity benefits under Title 35, to below and have also identification (s) on very least of the application (s) on the application (s) of the application (s) of the application (s) on the application (s) of the applica	United States Code §119 of any for ed below any foreign application for which priority is claimed:	reign app or patent	plication(s) for patent or or inventor's certificate
Prior Foreign Application(s)			Priorit	y Claimed
VI99A000202	ITALY	October 1, 1999	[X]	[]
(Number)	(Country)	Day/Month/Year Filed	Yes	No
(Number)	(Country)	Day/Month/Year Filed	[] Yes	[] No
(Number)	(Country)	Day/Month/Year Filed	[] Yes	[] No
I hereby claim the benefit listed below:	under Title 35, United State	es Code, §119 (e) of any United S	States pr	rovisional application(s)
Application No.	Day/Month/Year Filed	Application No.	Day/M	onth/Year Filed
each of the claims of this apparagraph of Title 35, United no Title 37, Code of Federal	designating the United Stat oplication is not disclosed in t d States Code, §112, I ackno	tates Code, §120 of any United es of America listed below and, in the prior application(s) in the manner owledge the duty to disclose material occurred between the filing date of ation:	nsofar as er provide al inform	s the subject matter of ed by the first lation as defined
* * * * * * * * * * * * * * * * * * * *				
Application Serial No.	Filing Date	Status (patented, pending, aban	doned)	

		Attorney Docket No.				
Application Serial No.	Filing Date	Status (patented, pending, abandoned	1)			
No. 27,297; Donald N. Huff, Charles Rutherford, Reg. No.	connected therewith Reg. No. <u>27,561;</u> Jol 18,933; Robert L. K William F. Kolakowsk	gent(s) to prosecute this application and to tra; Lawrence R. Radanovic, Reg. No. 23,077; nn P. DeLuca, Reg. No. 25,505; Sandra S. Selly, Reg. No. 31,843, Kevin M. Hinman, Resy, Reg. No. 41,908, all of Dykema Gossett P. (202) 522-8669.	Richard H. Tushin, Reg. Snapp, Reg. No. 41,444;			
Address all correspondence to 3306.	Dykema Gossett P	LLC, Suite 300 West, 1300 I Street, N.W., W	ashington, D.C. 20005-			
false statements and the like s	eved to be true, and f so made are punisha nat such willful false s	of my own knowledge are true and that surther that these statements were made with ble by fine or imprisonment, or both, under Setatements may jeopardize the validity of the linventor's Signature	the knowledge that willful			
RERUZZO Massimo	_	Joan Man	March 1, 2002			
Residence: VIA S. PIO X, 44 – 36027 ROSA' (VI) - ITALY Citizenship ITALIAN						
Post Office Address: SAME A	AS ABOVE					
Pull Name of Second, Joint In PAROLIN Gilberto		Inventor's Signature	Date March 1, 2002			
Residence: VIA T. ZANON	Citizenship ITALIAN					

Post Office Address: SAME AS ABOVE

Applicant or Patentee:
Serial or Patent No.:
Filed or Issued:
Title: BRAKING UNIT FOR BICYCLES
VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS (37 C.F.R. §1.9(f) AND 1.27 (c)) - SMALL BUSINESS CONCERN
hereby declare that I am
[X] the owner of the small business concern identified below:[] an official of the small business concern empowered to act on behalf of the concern identified below:
NAME OF CONCERN: <u>OFFICINE PAROLIN S.N.C. DI PAROLIN STEFANO, PERUZZO MASSIMO E C.</u>
ADDRESS OF CONCERN: VIA RAMON, 10 – 36028 ROSSANO VENETO (VI) – ITALY
hereby declare that the above identified small business concern qualifies as a small business concern as defined in 37 C.F.R. §121.3-18, and reproduced in 37 C.F.R. §1.9(d), for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control both.
hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled BRAKING UNIT FOR BICYCLES
by inventors PERUZZO Massimo and PAROLIN Gilberto
described in:
[X] the specification filed herewith
[] application serial no, filed
[] patent no. issued

Attorney's Docket No:



If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 C.F.R. §1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 C.F.R. §1.9(d), or a nonprofit organization under 37 C.F.R. §1.9(e). *NOTE. Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities (37 C.F.R. §1.27)

FULL	NAME						·			_	
ADDF		101		LL DUOM	F00 00N	OFDN	[] [N DD			7471011
	[]INDIVIDU	JAL	[]SMAI	LE ROZIM	ESS CON	CERN	[]NC	N PR	JFII	ORGANI	ZATION
FULL	NAME										
Those are	RESS										
	RESS [] INDIVIDU	JAL	[] SMALI	L BUSINE	SS CONC	ERN	[] NC	N PR	OFIT	ORGANI	ZATION
an a											
HULL 41	NAME							·		-	
	RESS									_	
	(] INDIVIDU	JAL	[]SMAL	L BUSINE	ESS CON	CERN	[] NC	N PR	OFIT	ORGANI	ZATION
Lackr	nowledge the	duty	to file in	this appli	cation or	patent	notifica	ation o	f anv	change	in status
result	ing in loss of	entitl	ement to	small entit	ty status p	orior to	paying	, or at	the ti	me of pa	ying, the
	st of the issu					e after t	the dat	e on w	vhich	status as	a small
entity	is no longer a	appro	priate. (3	7 G.F.R. 9	1.20(0))						
stater stater punisi Code	eby declare to nents made nents were mable by fine and that suctissuing there	on ir nade v or im ich wi	nformation with the ki prisonme Ilful false	n and beli nowledge nt, or both statement	ief are be that willful n, under se ts may jec	elieved I false s ection 1 opardize	to be statement of the	true; ents and Title fralidity	and found the second t	further the like so note the Unite e applica	at these nade are ed States
NAME	OF PERSO	N SIG	NING <u>P</u>	ERUZZO	Massimo	-					
TITLE	OF PERSOI	N OT	HER THA	N OWNER	R						
ADDF	RESS OF PE	RSON	SIGNING	G <u>VIA S.</u>	PIO X, 44	- 3602	27 ROS	6A' (VI)	<u> </u>	ALY	
SIGN	ATURE X	6	0000	L	2	DATE_	Februa	ry 28,	.200	2_	